



## Contec 21.5" Industrial Touch Monitor Model ITM2150

Photo



ID Type		True Flat(P-Cap)
Panel Spec	Model Name	ITM2150
	Type	AHVA
	Resolution	1920(H)x1080(V)
	Screen Size (inch)	21.5
	Display Area (mm)	476.06(H)x267.79(V)
	Pixel Pitch (mm)	0.247(H)x0.247(V)
	Viewing Angle (degree)	178(H)/178(V)
	Response Time (ms)	14 (On/Off)
	Brightness (cd/m <sup>2</sup> )	250 (Typ.)
	Contrast Ratio	1000:1 (Typ.)
Color Depth (bits)	8	
I/O Interface	DVI	N/A
	DP	DP1.2 x1
	VGA	N/A
	HDMI	HDMI1.4 x1
	USB Hub	USB Type-A x2
	Audio	Ear Phone x1
Touch/Glass	Type	P-Cap
	Touch Point	10
	Screen Printing	Black
	Glass Coating	Clear
Features	Interface	USB
	Color Temperature	Ne utral/W arm/Cool/User
	OSD Languages	English/French/German/Italian/Spabish/Japanese
	Scaling Mode	Full Screen
	Speaker	2W Speaker
	Convenience	N/A
	Others	N/A
Power Requirements	Power Supply	AC 100~240V
	Power Consumption (W)	25W
Physical Characteristics	Dimensions (W×H×D) (mm)	521.05x373.24x228.86 ( with Stand) 521.05x312.5x52.7 (without Stand)
	VESA Mounting (mm)	100x100
	Weight (Kg)	5.8 (with Stand) 4.2(without Stand)
	ID Color	Black
	IP Rating (Front)	IP65
	IP Rating (Back Cover)	IPX2
	Tilt Range (degree)	-5~+23
	Pivot Range (degree)	N/A
	Swivel Range (degree)	N/A
Height Adjustment (mm)	N/A	
Reliability	Operating Temperature(°C)	10 to 40
	Operating Humidity (RH)	30% to 75%
	Storage Temperature (°C)	-20 to 60
	Storage Humidity (RH)	10% to 90%
Certifications and Compliances		cTUVus 62368-1;CAN/CSA-C22.2 62368-1 CB(IEC 62368-1), CE(EN55032;EN55035;EN62368-1) FCC Part15,ROHS,WEEE