

Photo



ID Type		True Flat(P-Cap)
Panel Spec	Model Name	M238HVN01.0
	Type	MVA
	Resolution	1920(H)x1080(V)
	Screen Size (inch)	23.8
	Display Area (mm)	527.04(H)x296.46(V)
	Pixel Pitch (mm)	0.274(H)x0.274(V)
	Viewing Angle (degree)	178(H)/178(V)
	Response Time (ms)	16 (On/Off)
	Brightness (cd/m ²)	250 (Typ.)
	Contrast Ratio	3000:1 (Typ.)
Color Depth (bits)	8	
I/O Interface	DVI	N/A
	DP	DP1.2 x1
	VGA	D-Sub15 x1
	HDMI	HDMI1.4 x1
	USB Hub	USB Type-A x2
	Audio	Ear Phone x1
Touch/Glass	Type	P-Cap
	Touch Point	10
	Screen Printing	Black
	Glass Coating	Clear
	Interface	USB
Features	Color Temperature	Ne utral/W arm/Cool/User
	OSD Languages	English/French/German/Italian/Spabish/Japanese
	Scaling Mode	Full Screen
	Speaker	2W Speaker
	Convenience	N/A
	Others	N/A
Power Requirements	Power Supply	AC 100~240V
	Power Consumption (W)	30W
Physical Characteristics	Dimensions (W×H×D) (mm)	571.43x387.42x228.86mm (with Stand) 571.43x340.86x52.7 (without Stand)
	VESA Mounting (mm)	100x100
	Weight (Kg)	7 (with Stand) 5.4(without Stand)
	ID Color	Black
	IP Rating (Front)	IP65
	IP Rating (Back Cover)	IPX2
	Tilt Range (degree)	-5~+23
	Pivot Range (degree)	N/A
	Swivel Range (degree)	N/A
Height Adjustment (mm)	N/A	
Reliability	Operating Temperature(°C)	10 to 40
	Operating Humidity (RH)	30% to 75%
	Storage Temperature (°C)	-20 to 60
	Storage Humidity (RH)	10% to 90%
Certifications and Compliances		cTUVus 62368-1;CAN/CSA-C22.2 62368-1 CB(IEC 62368-1), CE(EN55032;EN55035;EN62368-1) FCC Part15,ROHS,WEEE